Touch

With Nexus Stand

Getting Started Guide

Follow this guide to set up your Touch Nexus as a freestanding, heavy duty base, adhesive or screw mounted tablet stand.

Contents

Touch Holder	3
Screw Mounting	5
Freestanding & Adhesive Mounting	7
Optional Extras	10

Touch

Follow these steps to attach your tablet to the Touch holder. Locate the below items along with your tablet device and charging cable and continue to Step 1.



Touch holder




Nexus stand



Security key




x4 M4
Screws




Step 1 Locate the Touch holder and unscrew the security screw to remove the top bracket that holds the adhesive.



Step 2 Attach the Touch holder to the stand and screw in the x4 screws to secure.



Step 3 Peel off the adhesive paper from the top bracket.




Step 4 Place the bracket in the center of the tablet and press down and hold for 20 seconds.

Screw Mounting

Firstly, ensure you have followed the steps on page 2 to attach your tablet to the Touch holder before continuing.

Follow these steps for counter top mounting. Locate the below items along with your tablet (with Touch holder attached) & charging cable.



Touch holder




Nexus stand




Security key




x2 Wood Screws




Step 1 Locate the Nexus stand and follow the above locations to line up your surface mounting & cable feed.




Step 2 Drill pilot holes to assist with screw base mounting. Refer to the mounting guide for assistance.




Step 3 If you are running your charging cable through the surface, ensure to drill a larger hole to feed cable through.



Step 4 With the cable channel facing out the left hand side of the stand, screw down your stand using the wood screws provided.



Step 5 Feed Charging Cable through the stand and plug it into the tablet



Step 6 Attach your tablet with Touch bracket attached. Secure with Security Key and screw.

Freestanding & Adhesive Mounting

Firstly, ensure you have followed the steps on page 2 to attach your tablet to the Touch holder before continuing. Follow these steps for counter top mounting.

Locate the below items along with your tablet (with Touch holder attached) & charging cable to begin. If you are not using Heavy Duty Base, skip to **Step 2**.



Touch holder



Nexus stand




Security key




Heavy Duty Base (Add on)




x2 Base Screws (Add on)



Step 1 With the cable channel facing out the left hand side of the stand, screw down your stand to the Heavy Duty Base.



Step 2 Feed charging cable through stand and plug in tablet.




Step 3 Attach your tablet with Touch bracket attached. Secure with Security key and screw.


Follow steps 4-6 for adhesive mount instructions.



Step 4 Wipe base of stand & your mounting surface with alcohol wipes provided & let dry.




Step 5 Stick 3M adhesive to the base of stand & firmly place down on your mounting surface.



Step 6 Let the stand sit for 24 hours before use.

Optional Extras

Follow this step to install the position lock to disable 180° swivel movement.



Nexus Stand Position Lock Rotate stand 45 degrees so cable hole is on the left, then screw in lock screw as shown. This will lock the rotation for a fixed option.

US Customer Support
1800 293 9703
sales@bosstab.com

Australia Customer Support
1800 870 132
sales@bosstab.com.au

Warranty & Returns If you receive an item that is faulty or damaged then you can send it back for a refund, replacement or store credit & we'll pay for the return postage costs. We offer a 12 month warranty on items that are deemed defective by the manufacturer. If you have a defective product covered by this warranty, we will either repair using new or refurbished parts, or if repair is not possible, replace the item. The warranty will not cover loss or theft, nor damage deemed to be caused by misuse or unauthorized modification. To view our full returns policy & initiate a return please visit **www.bosstab.com**