

VESA

With Nexus Pole

Getting Started Guide

Follow this guide to set up your VESA Nexus as a freestanding, heavy duty base, adhesive or screw mounted tablet stand.

Contents

Screw Mounting	3
Freestanding & Adhesive Mounting	6
Optional Extras	9

Screw Mounting

Follow these steps for counter top mounting. Locate the below items along with your device and charging cable to begin.



VESA Mount



Nexus Stand




x4 Pan Head
Screws




Step 1 Locate the Nexus stand and follow the above locations to line up your surface mounting & cable feed.


Step 2 Drill pilot holes to assist with screw base mounting. Refer to the mounting guide for assistance.




Step 3 If you are running your charging cable through the surface, ensure to drill a larger hole to feed cable through.




Step 4 With the cable channel facing out the left hand side of the stand, screw down your stand using the wood screws provided.




Step 5 Locate the VESA mount and attach to the hinge by screwing in the x4 screws to secure.



Step 6 Feed cable up through the hinge pole. Ensure enough length is fed through to easily plug into your monitor.



Step 7 Attach your VESA compatible device by screwing in from the rear. Plug cable into monitor.



We have supplied x4 Pan Head Screws to assist with mounting your VESA compatible device. Ensure to follow instructions on your device to use the correct screws.

Freestanding & Adhesive Mounting

Locate the below items along with your device and charging cable and continue to begin. If you are not using Heavy Duty Base, skip to **Step 2**.



VESA Mount



Nexus stand




Heavy Duty
Base
(Add on)




x2 Base
Screws
(Add on)




x4 Pan Head
Screws




Step 1 With the cable channel facing out the left hand side of the stand, screw down your stand to the Heavy Duty Base.



Step 2 Locate the VESA mount and attach to the hinge by screwing in the x4 screws to secure.



Step 3 Feed cable up through the hinge pole. Ensure enough length is fed through to easily plug into your monitor.



Step 4 Attach your VESA compatible device by screwing in from the rear. Plug cable into monitor.

Follow steps 5-7 for adhesive mount instructions.




We have supplied x4 Pan Head Screws to assist with mounting your VESA compatible device. Ensure to follow instructions on your device to use the correct screws.



Step 5 Wipe base of stand & your mounting surface with alcohol wipes provided & let dry.




Step 6 Stick 3M adhesive to the base of stand & firmly place down on your mounting surface.



Step 7 Feed cable up through the hinge pole. Ensure enough length is fed through to easily plug into your monitor.

Optional Extras

Follow this step to install the position lock to disable 180° swivel movement.



Nexus Stand Position Lock Rotate stand 45 degrees so cable hole is on the left, then screw in lock screw as shown. This will lock the rotation for a fixed option.



US Customer Support

1800 293 9703

sales@bosstab.com

Australia Customer Support

1800 870 132

sales@bosstab.com.au

Warranty & Returns If you receive an item that is faulty or damaged then you can send it back for a refund, replacement or store credit & we'll pay for the return postage costs. We offer a 12 month warranty on items that are deemed defective by the manufacturer. If you have a defective product covered by this warranty, we will either repair using new or refurbished parts, or if repair is not possible, replace the item. The warranty will not cover loss or theft, nor damage deemed to be caused by misuse or unauthorized modification. To view our full returns policy & initiate a return please visit www.bosstab.com